



PTB750S-03-5

TECHNICAL DATA

| | |
|-------------------|-----------|
| PITCH | 7.62mm |
| ELECTRICAL RATING | 300V, 15A |
| BREAKDOWN VOLTAGE | 4,000V |

MATERIALS

| | |
|-----------------------|-------------------|
| INSULATION BODY | Nylon,UL94,V-0 |
| TERMINAL | Brass, Tin Plated |
| OPERATING TEMPERATURE | -40°C ~ +105°C |
| PCB HOLE DIAMETER | ø1.6mm |

*MATE WITH PLUG: PTB750B-03-5

| Positions | L | Positions | L |
|-----------|--------|-----------|--------|
| 02 | 15.24 | 18 | 137.16 |
| 03 | 22.86 | 19 | 144.78 |
| 04 | 30.48 | 20 | 152.40 |
| 05 | 38.10 | 21 | 160.02 |
| 06 | 45.72 | 22 | 167.64 |
| 07 | 53.34 | 23 | 175.26 |
| 08 | 60.96 | 24 | 182.88 |
| 09 | 68.58 | | |
| 10 | 76.20 | | |
| 11 | 83.82 | | |
| 12 | 91.44 | | |
| 13 | 99.06 | | |
| 14 | 106.68 | | |
| 15 | 114.30 | | |
| 16 | 121.92 | | |
| 17 | 129.54 | | |

ORDERING INFORMATION

| | | | | | |
|--|---|----------------------------------|---|---|---|
| SERIES | STYLE | PITCH | POSITIONS | COLOR | OPTIONS* |
| PTB <input type="text"/> <input type="text"/> <input type="text"/> S | — <input type="text"/> <input type="text"/> | — <input type="text"/> | — <input type="text"/> <input type="text"/> | — <input type="text"/> | — M <input type="text"/> <input type="text"/> |
| | 00 to 99 | 1=5.00mm 2=5.08mm 5=7.62mm | 02 to 24 | 0=Light Grey 1=Black 2=Blue 3=Green 4=Dark Grey | |