



PTB750S-05-5

TECHNICAL DATA E183240 C228277

PITCH	7.62mm
ELECTRICAL RATING	300V, 15A
BREAKDOWN VOLTAGE	4,000V

MATERIALS

INSULATION BODY	Nylon,UL94,V-0
TERMINAL	Brass,Tin Plated
OPERATING TEMPERATURE	-40°C ~ +105°C
PCB HOLE DIAMETER	ø1.6mm

*MATE WITH PLUG: PTB750B-05-5

Positions	L	Positions	L
02	15.24	18	137.16
03	22.86	19	144.78
04	30.48	20	152.40
05	38.10	21	160.02
06	45.72	22	167.64
07	53.34	23	175.26
08	60.96	24	182.88
09	68.58		
10	76.20		
11	83.82		
12	91.44		
13	99.06		
14	106.68		
15	114.30		
16	121.92		
17	129.54		

ORDERING INFORMATION

SERIES	STYLE	PITCH	POSITIONS	COLOR	OPTIONS*
PTB <input type="text"/> <input type="text"/> <input type="text"/> S	<input type="text"/> <input type="text"/>	<input type="text"/>	<input type="text"/> <input type="text"/>	<input type="text"/>	M <input type="text"/> <input type="text"/>
	00 to 99	1=5.00 2=5.08	02 to 24	0=Light Grey 1=Black 2=Blue 3=Green 4=Dark Grey	